Swim 'n' Rinse Transom Shower

The classic design in deck showers for easy washdown on the transom after swimming. Simply swim and rinse without wasting water.

Only suitable for pressure systems up to 45psi /3 bar Save water on board -Simply use the hot and cold controls - mix perfect temperature then close the rose handset to conserve water supply during showering Easy use controls even with soapy hands - to set ideal temperature Standard connections - 1/2" connections/ suitable for Whale Quick Connect 15mm plumbing

Lightweight handset will not damage the gel coat if dropped on deck

Sleek cover - for a neat finish on deck

Robust ABS housing is designed and tested to withstand extreme marine conditions

- long life UV resistant

1 Year Warranty

COMPLETE YOUR SYSTEM

Freshwater system accessories such as water filters, and pipework connections – page 76-77

Lightweight and durable ABS exterior shower range

- add a touch of luxury on board
- Designed for easy rinse down after swimming
- Fit in convenient locations on deck
 extra long 2.1 m (7 ft) hose
- Save water on board On/off control on shower handset allows you to set temperature and only use the water you need
- · Neat hinged cover with latch to close
- White high shine finish matches the gel coat
- Available with/without cover
- Simple connection to either Quick connect 15mm pipework/ 1/2" hose connection

YOU MAY ALSO LIKE

Whale Twist® - Deck Shower with integrated Temperature and Flow Controls - page 72 Swim 'n' Rinse Compact - deck shower - Ideal where space is limited on deck - page 74 Watermaster Automatic Pressure Pumps - page 54 Whale® water filters - page 76


Product Information

Model Specifications

Weder openiodations				
Model	Cold Only (no cover)	Cold Only (cover included)	Hot and Cold Mixer (no cover)	Hot and Cold Mixer (cover included)
Product Code	RT1648	RT1649	RT2648	RT2658
Colour	White			
Base Plate	167 mm (6 ½") X 292 mm (11 ½")			
Depth Beneath Surface	88 mm (3 ½")			
Hose Connections	½" Male Threaded (BSP / NPT)			
Connection to Quick Connect 15 mm Plumbing	Use WX1532 - Adaptor Female ½" – 15 mm			

2.1 m (7 ft)

350mm (13 ½*)
180mm (7*)
167mm (6 ½*)
292mm
(11 ½*)
298mm
(11 ¾4*)



Note: These specifications are retail items only.

Hose Length

For details of our bulk pack range for boat builders and wholes alers - contact Whale Support. $\label{eq:contact}$

Note: only suitable for pressure systems up to 45psi /3 bar